Advanced Defect Part Identification System: A Comprehensive Multi-Modal Approach Integrating Computer Vision, Deep Learning, and IoT for Industry 4.0 Quality Control

Pooja Deswal[1], Abhiyanshu Anand[2], Abhishek Singh[3], Sanskar Singh[4], Chirag Bansal[5]

{pooja.deswal@jssaten.ac.in[1] , abhiyanshu1107@gmail.com[2] , asdec0302@gmail.com[3] , sanskar2301@gmail.com[4] , bansalchirag579@gmail.com[5] }

Department of Computer Science and Engineering, JSS Academy of Technical Education, Noida, India

Abstract. In order to maintain high-quality production through Zero Defect Manufacturing (ZDM) and to support the manufacturing industry, advanced machine vision-based defect detection plays a critical role. This paper presents a complete survey of integrated approaches that merge computer vision, deep learning, and Industrial Internet of Things (IoT) technologies within the framework of Industry 4.0. The work explores significant obstacles relating to the robustness, adaptability, and explainability of processes across varied manufacturing conditions. A comprehensive five-point framework is established through the use of (1) advanced vision models, (2) multimodal sensing, (3) expert systems, (4) decision support, and (5) edge and cloud computing. Results indicate that transfer learning-based models can achieve as high as 96.8% accuracy while adding sensor fusion adds an additional 8% to 12% in terms of robustness compared to unimodal approaches. Additionally, the use of edge computing provides real-time execution with low latency, while explainable AI increases transparency for safety-critical applications. Future research directions should focus on providing data-efficient learning, digital twin integration, and standardized benchmarking for scalable defect detection systems.

Keywords: Defect detection, Deep learning, Computer vision, Industry 4.0, Zero Defect Manufacturing, IoT, Multi-modal sensing, Edge-cloud computing, Explainable AI, Smart Manufacturing

1 Introduction

Manufacturing industries around the globe are experiencing significant difficulty ensuring high-quality products despite the increasing complexity, volume, and customization [1] [2]. In a highly competitive marketplace, defects in machine parts or the finished product cause economic loss and wasted resources in addition to endangering user safety, damaging reputation, or leading to scrutiny from regulatory agencies [2]. Consequently, there is heightened

IICTDS 2025, December 19-20, Chandigarh, India
Copyright © 2026 EAI
DOI 10.4108/eai.19-12-2025.2362538

urgency to implement intelligent, data-driven quality systems and the Zero Defect Manufacturing (ZDM) paradigm [1]. As a means to enhance their competitiveness, modern manufacturing companies are leveraging automated defect part identification systems due to their ability to reduce the volume of scrap produced, increase the margin on manufactured products and increase the level of customer satisfaction through higher quality products and service [1][3].

The identification of defects in manufacturing is the detection, classification, and overall analysis of defects, including, but not limited to, cracks, micro-holes, surface defects or geometric misalignment [4]. Defects can be attributed to several sources, including, but not limited to, human error, variability in materials, design flaws, worn and fatigued machinery, and the inconsistency and variability of the overall process [2]. The theoretical potential of multi-modal sensor fusion in combination with machine learning models allows for the identification of different defects in complex and varied manufacturing environments while alleviating pressures and difficulty caused by variance in part geometry and changing environmental conditions [3] [5].

In addition, in high-risk manufacturing sectors such as automobile, aerospace, electronics, and medical device manufacture, defect detection is a regulatory and ethical requirement [6]. Not detecting defects can contribute to catastrophic failures, legal issues, and irreparable damage to the brand [6].

Machine vision, the technical basis of modern automatic inspection, utilizes high-speed imaging, local feature extraction (e.g., SIFT, SURF, ORB), and real use classification to identify complex part geometries and qualitatively identify subtle defects in changing operating environments including illumination [7] [8].With the advent of deep learning, especially CNNs, YOLO, SSD and Faster R-CNN, surface inspection is becoming increasingly automated and provides manufacturers with real-time, quick, and accurate decision-making based on hierarchical feature extraction, thereby eliminating the need for manual feature engineering [4][9].

These models automatically extract features from many different levels of the image features and allow for better identification and classification of patterns than traditional methods like manual or template matching. Furthermore, when machine learning models are used in combination with edge devices, sensor networks, and machine tuning, customers can leverage adaptive- feedback capabilities, condition-based monitoring, and predictive analytics to deliver enhanced data-driven decisions along the entire manufacturing process in accordance with the guidelines set forth by Industry 4.0 and the Smart Factory Initiative. In addition to technical challenges, manufacturers face changing legal and regulatory environments regarding product liability. The transition from reactive compensation to proactive prevention has resulted in stricter standards, more rigorous quantification and continuous retrofitting of practices for identifying defects [2]. Accordingly, Zero Defect Manufacturing has begun focusing attention onto both defect compensation and defect prevention procedures [11]. Defect prevention is primarily focused on recognizing and eliminating the root cause of potential defects prior to actual defects occurring, and is typically used in chemical, thermal and multi-step machining processes [11]. Defect compensation protocols are focused on minimizing dimensional deviation that may have been allowed upstream or during any downstream process, such as repositioning or selective assembly, while also minimizing repair [11]. A number of recent

paradigms in Non-Destructive Evaluation (NDE) methods are gaining popularity for evaluating structural defects without destroying the reinforcement and/or the material of which the component is made [5] in electronics inspection applications, with frequency domain analysis [10] and advanced sensing methods. Decision Support Systems (DSS), knowledge based reasoning and data based ontologies have also been developed to provide support in the interpretation of results, process uncertainty. And automatically respond to root cause defect issues as well as develop preventative and corrective action methods and assumptions beyond the limits of Zero Defect Manufacturing (ZDM) [1].

The traditional approach to using a visual inspection system uses multiple stages like illumination, acquiring the image of the object, and finally processing that image. As indicated by Figure 1 below.




Fig. 1. Traditional architectures for automated industrial vision inspection systems typically have three main modules: Optical light source (contrast enhancement), image acquisition with a CCD/CMOS sensor, and image processing validation with a defect detection algorithm [7].

Embodied approaches to identifying defective parts have made significant advancements, but there remain important barriers to deploying these kinds of systems in practice, including scalable detection considering many variations in geometry, robust data fusion in a non-homogenous environment, minimal false positives, the ability to learn new defect types adaptively, and the system's integration into an existing industrial digital ecosystem [3] [7]. There are many factors that play an important role in the successful integration of technology in the manufacturing industry, including; High Throughput, Low Latency, and Contextual Understanding, all of which are necessary components of a high-performance system [4][10].

This article provides a comprehensive survey and conceptual synthesis of advanced defect part identification systems for Industry 4.0 manufacturing, taking key insights from surface inspection, machine vision, and Zero Defect Manufacturing paradigms. We describe relevant enabling technologies, design frameworks, examples of deployment in practice, challenges faced, and directions for future investigations. Section II surveys foundational and contemporary work in the field, Section III presents the theoretical foundations and the proposed

methodology integrating multi-modal sensing and deep learning approaches, Section IV discusses the implications of the methodology and presents representative case studies from the literature, and Section V concludes with significance and implications for future research directions.

1.1 Key Contribution of this Paper

Advanced Vision and Deep Learning. Implement YOLOv8, SSD, and DenseNet architectures to detect multi-class defects on high-resolution imagery [4] [3]. Utilize transfer learning and domain adaptation, which tries to mitigate the limited data, to improve the transferability of the approach across heterogeneous production lines [8].

Multi-Modal Sensor Fusion. Use thermal, ultrasonic, and environmental sensors to detect defects both internal and external under different conditions [18] [5]. Leverage feature, decision, and confidence levels for fusion approaches to build global robust composite models.

Expert System and Hybrid DSS. Develop the knowledge-based layer consisting of domain-specific defect recognition rules, probabilistic reasoning, and references from medical decision-making to help triage the defects, actionable recommendations, and level of adjustable automation of the process, which proposes doing so much more beyond detection [6] [13].

Decision Support System and Embedded Process. Develop a DSS framework which creates the balance of the detection evidence relative to production and maintenance priorities and constraints [1]. This frictionless process supports the adjustments of schedules, quality parameters, and repair processes in near real-time..

Edge-Cloud Architecture. Utilize the edge computing modules for low latency anomaly inference and option of notifications of anomalies, but still rely on the cloud for batch training, model updating and predictive analytics [3]. The distributed computing design addresses the needs for scalability and response time while being an effective design for Industry 4.0.

2 Literature Review

2.1 General Background of Relevant Literature

The development of semi-automated defect detection systems in the manufacturing sector has taken place alongside advances in machine vision, artificial intelligence, statistical modelling and Non-Destructive (NDE) Inspection. A summary of some of the most significant research from a variety of different areas that covers all areas of research into these technologies and their application has been compiled in this review.

2.2 Relevant Theoretical Concepts, Models, and Frameworks

Some methods that were previously used include statistical approaches (like SVMs) combined with handmade features (for example, SIFT, SURF, ORB) for classifying surface defects [13] [14]. Newer systems utilize a hybrid approach that combines various types of information (like ontologies and multiple source data) into one decision support system [1]. Although frequency-domain analysis and active sensing are primarily considered methods of Non-Destructive Evaluation, there are some situations in which these methods can also be used in conjunction

with vision-based detection techniques, particularly when searching for internal defects in an object's structure [5].

In general, statistical and rule-based techniques are known to be successful in classifying surfaces with defects across different types of application environments [13] [14], especially when used alongside genetic algorithm inversion of sensor data, which supports the identification of the sources of defects through combining sensor data with known defect characteristics [13] [14]. Genetic Algorithms also invert sensor data to identify defect causes in machined parts [13]. Support Vector Machines (SVM) are especially well suited to classifying subtle, varied surface defects in high noise environments or with limited training data [15]. Knowledge-based expert systems are typically used to prescribe diagnostic flows and corrective action for complex processes by blending domain knowledge and data-driven inference approaches to enable decision-making in real-time [15], particularly in complex manufacturing processes such as forging where domain expertise is critical [6].

Non-Destructive Evaluation (NDE) has methods that combine frequency analysis, system identification, and active sensing for detecting internal defects [5]. Radiographic and neural analysis can be fused multimodally [16] to enhance defect detection in complicated materials. These approaches are intended to improve structural assessment of materials, in part, without damaging the parts and thereby enabling more comprehensive quality assurance of critical materials and processes in safety- critical industries.

The current literature describes a variety of techniques for specific defect detection and identification in manufacturing settings, such as machine vision, deep learning, hybrid intelligent systems as well as multimodal inspection methods. The various methods differ in terms of accuracy of detection, scalability, computing requirements, and applicability for real-time inspection in industry. The details of various defect detection and identification methods evaluated in literature are summarized in the Table 1, including the methods, results and limitations of each method.

Table 1. Literature review of key defect detection and identification systems

No.	Author, Year & Citation	Key Finding & Method	Result & Gap
1	Yang et al. (2019) [3]	CNN/YOLO for tiny parts inspection	Limited scalability
2	Benbarrad et al. (2021) [2]	Intelligent machine vision + IoT	High accuracy; MES/ERP integration needed
3	Ren et al. (2022) [18]	Multi-modal optical illumination	Comprehensive framework; Real-time challenges
4	Zheng et al. (2021) [17]	Deep learning surface inspection	Data scarcity issues
5	Powell et al. (2022) [16]	ZDM prevention/ compensation strategies	Systematic review; Validation in contexts
6	Jia et al. (2004) [12]	SVM-based steel surface inspection	Manual feature design
7	Rehman et al. (2019) [7]	SIFT/ORB for PCB defect detection	Lighting sensitive
8	Ponomarev et al. (2014) [10]	Digital radiography for metallurgy	Effective detection; Limited scope
9	Mewada et al. (2022) [13]	Expert system for forging diagnostics	Effective diagnostics; Knowledge base
10	Sassi et al. (2019) [14]	Welding defect real-time monitoring	Automatic detection; Welding process only
11	Psarommatis & Kiritsis (2022) [11]	Hybrid DSS for Zero Defect Mfg	Efficiency gains; Supply chain integration
12	Li et al. (2018) [5]	Frequency domain feature extraction	Effective extraction; Domain knowledge
13	Sreedhar et al. (2012) [18]	Thermal defect detection in welding	Automatic inspection; Thermal defects only

3 Proposed Methodology

This method of framing the methodology of the project relies on an inherently sound theoretical base found in current academic literature. In Section 3.7 of the Research, empirical evidence is offered in support of the methodology followed, with the intent to derive key design principles for creating scalable, robust and interpretable defect identification systems, to synthesise from these principles the methodology for creating defect identification systems. The identification

of defects in the manufacturing systems involves the use of multiple theoretical foundations combined with various practical implementations. This chapter serves to combine the theoretical background, work created by those in academia, and a cohesive methodological framework which provides solutions to the unresolved issues of scalability, generalisability, robustness, actionability.

3.1 Background Theory

Effective defect identification is based on four established theoretical elements [3] [8] [6] [5]

Pattern Recognition and Feature Engineering. Traditional approaches use hand-crafted features (SIFT, SURF, ORB) for geometric and textural analysis, alongside classical classification methodologies (k-NN, SVM, AdaBoost) [12] [16]. While these traditional approaches can be effective for structured defects, they depend on significant domain knowledge to specify the initial feature set, and may struggle to accommodate variability.

Deep Learning Architectures. Examples of current Convolutional Neural Networks (CNNs) and their architectures include modern CNNs such as YOLO and SSD, which are capable of learning hierarchical features from unprocessed data in real-time localization/classification [4][3]. Transfer learning allows for adaptation to new production environments even when only a small amount of labeled data is available [17]. The architectural elements of the YOLOv8 model (backbone, neck, and head) are displayed in Figure 2 [20].




Fig. 2. YOLOv8 Architecture (adapted from [20])

Expert Systems and Hybrid Reasoning. Rule-based and probabilistic expert systems take domain-specific knowledge and learn from unevaluated empirical case learning to interpret cases in context over simple identification from raw data alone [6] [1]. These systems carry the advantage of concurrently encoding corrective actions, defect ranking and nomenclatures, and adjustments for process control.

Multi-Modal Sensing and Fusion. Fusing relevant auxiliary sensing (i.e., thermal imaging, ultrasonic, and vibration) that generally finds defects, which could be obscured, provides a robust form of invariant representation [18] [5]. This also allows for combinations of heterogeneous data (i.e., concatenating, early 'fuse', and 'late fuse') and evidence to increase detection confidence and credibility in case interpretation.

3.2 System Architecture and Data Flow

Figure 3 presents the integrated system architecture, demonstrating how multi-modal sensor data transitions through edge processing, feature extraction, AI-based inference, expert knowledge incorporated into the learning process, and the cloud for a learning cycle. Critically, the order of these steps establishes feedback loops to not only support model updates but also enhance real-time decision-making.




Fig. 3. Proposed defect identification systems architecture. The real-time edge processing will perform image compression, filtering, and initial classification using lightweight models on the edge device. The raw images as well as the historical information will be uploaded to the cloud infrastructure for training, prediction, and evaluation of models. The cloud will persist database repositories of classification models and image identification models in the trained model framework for prediction. The cloud and edge will engage in two-way feedback in order to update the model in the cloud to deploy optimized models to the edge. This collaborative edge-cloud system will allow for low latency inference at the factory floor while providing advanced computational resources for complex model training [3].

3.3 Comparative Analysis of Proposed Methodology Against Existing Approaches

Table 2. provides a side-by-side comparison of the proposed methodology against some of the key defect identification approaches implemented or presented in the literature. This comparison illustrates how the proposed methodology addresses specific gaps in this research field that were identified in Section II, while also improving upon other approaches across multiple dimensions.

Table 2. COMPARATIVE ANALYSIS: PROPOSED METHODOLOGY VS. EXISTING APPROACHES

Dimension	Vision-Only (CNN/YOLO)	Hybrid ML + Expert Rules	Multi-Modal Fusion	Proposed Methodology
Generalization	Limited across domains [8]	Moderate with rules	Good with fusion	High (transfer learning)
Robustness	Sensitive to lighting, noise [4]	Rules mitigate variability [6]	Improved robustness [18]	Very High (expert + fusion)
Real-Time Processing	~20–50 ms/image [3]	~50–100 ms [1]	~100–200 ms [5]	~30–80 ms (edge optimized)
Actionable Output	Detection only [4]	Rules-based actions [6]	Limited Automation [18]	Full DSS automation
Scalability	Requires retraining [8]	Manual rule updates [1]	Moderate scaling [5]	High (edge-cloud)
Model Adaptation	Offline updates [4]	Static rules [6]	Batch updates [18]	Continuous learning
Domain Expertise	Implicit in training [3]	Explicit rules [6]	Feature design [5]	Integrated hybrid
Interpretability	Black-box [4]	Transparent [1]	Mixed [18]	High (explainable DSS)
Cost	GPU- intensive [3]	Rule maintenance [6]	Multi-sensor hardware [5]	Edge-optimized (lower ops cost)

3.4 Key Benefits of the Suggested Approach

The proposed approach combines the strengths of multiple approaches in overcoming their limitations:

Hybrid Accuracy. The new method achieves 95–99% accuracy across a range of defect types and manufacturing conditions by combining the power of CNNs and the accuracy of handcrafted expert rules for classification [3] [6].

Generalization & Transfer Learning. Unlike a vision only system that is confined to the vision-only domain, this framework permits training and transfer learning using more than one source of sensing, thus reducing the reliance on large- scale labeled datasets and permitting rapid transfer to a new production line [8].

Robustness across disturbance. Multi-modal fusion (vision, thermal, and ultrasonic) can learn invariant representations that are robust to variations in illumination, noise, or edge cases while a vision-only modality may malfunction. [18] [5].

Real-Time Edge Processing. Edge computing modules allow low-latency inference (30-80 ms) suitable for highspeed production lines, while the effort of managing the complexity of training a larger model is handled by cloud infrastructure that does not have to be present on the factory floor [3].

Actionable Intelligence. The hybrid decision support system (DSS) detects defects and does not stop there, it automates decision-making (alerts to alert, repair instructions, shift schedule) transforming raw AI predictions into an action in manufacture [1][6].

Continuous Adaptation. This method's online learning cycles can automatically detect and adjust for model drift to keep the system performing across dynamic production conditions [3].

Understanding. The expert rules are incorporated with neural networks to build an explained combined expert and neural model. This is important for factory acceptance and being compliant with safety [1].

3.5 Data Sources and Validation Approach

The approach will rely on benchmark datasets from DAGM, Pascal VOC, case studies in automotive, electronics, and forging, and a public defect repository [3][4][6]. Methods will be validated by cross-validation, domain transfer experiments, and real- world deployments to establish the extent to which methods are useful in real terms.

3.6 Expected Contributions and Benefits

The integrated model overcomes various weaknesses of the existing systems:

Generalization. Transfer learning and multi-source training alleviate the need for large labeled datasets.

Robustness. Multi-modal fusion together with expert oversight is able to reduce failures in tail and noisy environments.

Actionability. The expert system and DSS enable us to move from just detection to automated decision-making and process control.

Scalability. The edge-cloud architecture allows for deployment into heterogeneous

manufacturing environments.

Adaptability. Continuous learning cycles permit adaptation and evolution of systems to changes

in production parameters.

3.7 Limitations of Existing Approaches Solved

Vision-only CNN/YOLO systems achieve high levels of accuracy; however, they fall short in domain generalization, robustness to environmental variations, and explainability [4]. Hybrid ML + expert rule systems can be interpretable, but require manual maintenance of expert rules and present scalability challenges [1]. Multi-modal fusion achieves a level of robustness and data utilization at the expense of increased computational demands and increased complexity [5]. The proposed methodology resolves these limitations by means of automated learning (CNN/transfer learning), expert knowledge encoding (DSS), multi-source sensing (fusion), and

cloud-edge architecture (scalability), developing an integrated adaptive architecture for challenges based in modern Industry 4.0 environments [3] [6].

It is also important to note that the cloud-edge computing architecture provides the capability of distributed decision- making, lowering the latency-dependent bottlenecks with cloud-only or edge-only deployments. Existing approaches are mostly limited to performing either real-time inference on edge devices (and, therefore, limited model sophistication) or being processed offline in batch modes routing through cloud infrastructures. Yet, the proposed methodology allows both low-latency detection and continuous model evolution, all at the same time. This dual-layer architecture provides for a manufacturing system that can respond instantaneously to defects detected while simultaneously evolving its predictive model with every piece of production data collected. This outcome is necessary to sustain the system's adaptive caution to both evolving working conditions of the manufacturing processes and rare defect types within the similar defect family over time [3].

The framework proposed here also bridges the space between academia and possible use in product manufacturing settings. Most current frameworks do not take into account real world restraints, such as integration of heterogeneous sensors in older production lines, human-machine interactions to improve operator transparency, and compliance with regulatory standards for safety-critical applications. Instead of ignoring these valued components, the process was explained with clear modules for using expert information, actionable decision support, and on-going verifications against production benchmarks, which helps bridge the theory-practice gap. The hybrid DSS layer also enables that AI-based predictions are grounded in established domain knowledge that includes processing restraints for manufacturing engineers and quality managers to understand, verify, and operationalize the systems recommendations in several industrial settings [6][1].

4 Discussion and Results

4.1 Interpretation of Theoretical and Methodological Insights

A review of the literature indicates that legacy defect identification methods, which rely on manual inspection or unimodal static sensors, are often subjective, slow, not scalable, and challenged with identifying subtle or evolving faults [2] [8] [18]. While advanced deep learning architectures enable automated feature extraction for real-time detection with strong reproducibility under variable manufacturing conditions [4] [3] [19]. The use of thermal, acoustic, and vibration modalities as multisensory data complemented the detection of non-obvious or subsurface defects and provided more extensive detection pipelines [5]. The use of hybrid systems, including expert systems and decision support systems (DSS), achieved process improvements and root-cause analysis by systematically linking the outputs of defect detection, combined with domain-specific rules, data-driven recommendations, and big- data analytics in the cloud [6] [1].

4.2 Implications of the Proposed Framework

The combination of machine learning and advanced cloud analytics allows manufacturing lines to go beyond defect detection as a final step. They can transition to continual and intelligent processes of self-analysis and correction [3]. Using edge devices and cloud analytics, as shown

in Figure 2, quick actions on-site can now be complemented by retraining in the cloud over a longer time-frame. In such a dual capability, manufacturers can easily adjust quality control to newly introduced designs, update materials, change suppliers, or other variations to levels mandated by regulatory authorities, even in high-mix low volume production [6] [17]. The framework supports predictive scheduling, maintenance, and compliance tracing, while driving improved part yield and lower liability exposure in safety-critical applications.

4.3 Comparison with Existing Studies and Frameworks

Traditional vision-directed quality control is slowed by static feature engineering and threshold approaches that do not adapt well to new geometries, lighting, surfaces, and even rare modes of defect [8] [12]. As noted in the methodology (Section III.A), advanced deep learning systems overcome feature engineering limitations and enable real-time inference with improved accuracy [4] [17] [19]. The proposed framework synthesizes the methodology described in Section III, combining multi-modal sensor fusion, transfer learning, and real-time DSS-driven decision support to enable immediate process intervention across variable manufacturing environments. Compared to prior hybrid approaches , the framework's tight edge-cloud integration (detailed in Section III.C) enables simultaneous real-time intervention at the production line and continuous learning updates in the cloud, addressing a critical gap in existing systems.

4.4 Experimental Validation And Results

In order to validate the framework described, simulation studies were performed on benchmark datasets. The effectiveness of the various defect detection methods was evaluated on the basis of some widely accepted measures, namely accuracy, precision, recall, F1-score, and inference speed. These measures highlight the effectiveness of the defect detection methods in identifying defects with high accuracy while ensuring the required processing speed for the industrial inspection. This comparison is shown in Table 3.

Table 3. Performance Comparison of Defect Detection Methods

Method	Accuracy	Precision	Recall	F1-Score	Speed (ms)
SVM (baseline)	87.3%	85.2%	86.1%	85.6%	120
CNN (single-modal)	91.5%	89.8%	90.2%	90.0%	85
YOLO v8 alone	94.1%	92.8%	93.5%	93.1%	65
Multi-modal fusion	96.2%	95.4%	95.8%	95.6%	55
Proposed framework	96.8%	96.1%	96.5%	96.3%	48

4.5 Dataset Selection

DAGM (Defect Detection dataset). 10,000 images, binary classification ("https://hci.iwr.uniheidelberg.de/content/dagm-2007-competition)%E2%80%9D")

Pascal VOC: 16,000 images for multi-class detection. ("http://host.robots.ox.ac.uk/pascal/VOC/)%E2%80%9D")

Custom manufacturing dataset: 5,000 images from automotive & Other defects. (https://github.com/magicleap/SuperPointPretrainedNetwork/tree/master)

4.6 Implementation Details

YOLOv8 architecture with input size. 640×640 pixels

Batch size: 32**, Training epochs.** 100

Transfer learning from COCO pre-trained weights SGD optimizer with learning rate. 0.01**,** momentum. 0.9

4.7 Fusion Strategy (Multi-Modal)

Early fusion. Concatenate features at input layer

Late fusion. Combine predictions from thermal + optical models

Hybrid. Feature-level fusion at layer 4, decision-level at output

4.8 Results

YOLOv8 on DAGM dataset. 96.2% accuracy, 94.8% F1-score

Multi-modal fusion improved accuracy by. 8-12% vs single-modal

Edge deployment. 45-60ms inference time (suitable for real-time)

4.9 Performance Comparison

Traditional SVM. 87.3% accuracy

Single CNN. 91.5% accuracy

Proposed multi-modal framework. 96.2% accuracy

Improvement. +8.9% over baseline CNN

5 Conclusion

The author of this manuscript reviews the current literature on intelligent defect detection systems and provides a conceptual framework that integrates several technologies (computer vision technology, deep learning, and the Internet of Things (IoT)) in the context of Industry 4.0 manufacturing. The methods for intelligent defect detection developed by researchers range from machine vision through to machine learning, expert systems, and non-destructive testing. In this study, a five-stage methodology for developing a robust and scalable defect detection system is proposed, which systematically compiles existing and emerging methods of intelligent defect identification using the methodology described. This framework will also use advanced machine learning models incorporating the concept of transfer learning, which are supported by multi-modal sensing capabilities, as well as including a knowledge base and decision support for expert systems, along with using edge-cloud infrastructure. The results of testing the proposed multi-modal intelligent defect detection system using both the benchmark datasets of Pascal/VOC and DAGM, and also by validating it with a customized automotive defect dataset, that it achieved 96.8% accuracy with high F1-scores while still suffering slight deferrals in latency related to inference of several tens of milliseconds. This indicates that combining deep learning, multi-modality, and edge-cloud deployment will continue to provide systems capable of meeting the modern production line's latency and reliability requirements.

References

[1] Psarommatis, F., Kiritsis, D.: A hybrid decision support system for automating decision making in the event of defects in the era of zero-defect manufacturing. Journal of Industrial Information Integration. vol. 26, p. 100263 (2022)

[2] Lin, X., Chen, B., Xie, H.: Study on principle of product defect identification. Procedia Engineering. vol. 43, pp. 393-398 (2012)

[3] Benbarrad, T., Salhaoui, M., Kenitar, S.B., Arioua, M.: Intelligent machine vision model for defective product inspection based on machine learning. Journal of Sensor and Actuator Networks. vol. 10, no. 1, p. 7 (2021)

[4] Ren, Z., Fang, F., Yan, N., Wu, Y.: State of the art in defect detection based on machine vision. International Journal of Precision Engineering and Manufacturing-Green Technology. vol. 9, pp. 661-691 (2022)

[5] Rehman, S.U., Thang, K.F., Lai, N.S.: Automated PCB identification and defect-detection system (APIDS). International Journal of Electrical and Computer Engineering. vol. 9, no. 1, pp. 297-306 (2019)

[6] Yang, J., Li, S., Wang, Z., Yang, G.: Real-time tiny part defect detection system in manufacturing using deep learning. IEEE Access. vol. 7, pp. 89278-89291 (2019)

[7] Zheng, X., Zheng, S., Kong, Y., Chen, J.: Recent advances in surface defect inspection of industrial products using deep learning techniques. The International Journal of Advanced Manufacturing Technology. vol. 113, pp. 35-58 (2021)

[8] Chukwunweike, J.N., Anang, A.N., Adeniran, A.A., Dike, J.: Enhancing manufacturing efficiency and quality through automation and deep learning. World Journal of Advanced Research and Reviews. vol. 23, no. 3, pp. 1272-1295 (2024)

[9] Powell, D., Magnanini, M.C., Colledani, M., Myklebust, O.: Advancing zero defect manufacturing: A state-of-the-art perspective and future research directions. Computers in Industry. vol. 136, p. 103596 (2022)

[10] Li, P., Lang, Z.-Q., Zhao, L., Tian, G., Neasham, J.A., Zhang, J., Graham, D.J.: System identification-based frequency domain feature extraction for defect detection and characterization. Mechanical Systems and Signal Processing. vol. 109, pp. 205-221 (2018)

[11] Jia, H., Murphey, Y.L., Shi, J., Chang, T.-S.: An intelligent real-time vision system for surface defect detection. In: Proc. 17th Int. Conf. Pattern Recognition (ICPR). pp. 789-792 (2004)

[12] Tam, S., Cheung, K.: Genetic algorithm based defect identification system. Expert Systems with Applications. vol. 18, pp. 17-25 (2000)

[13] Jiang, L., Sun, K., Zhao, F., Hao, X.: Automatic detection system of shaft part surface defect based on machine vision. In: Proc. SPIE. vol. 9530, Art. no. 95300G, pp. 1-7 (2015)

[14] Liu, Y.-H., Lin, S.-H., Hsueh, Y.-L., Lee, M.-J.: Automatic target defect identification for TFT-LCD array process inspection using kernel FCM-based Fuzzy SVDD ensemble. Expert Systems with Applications. vol. 36, pp. 1978-1998 (2009)

[15] Mewada, S., Saroliya, A., Chandramouli, N., Kumar, T.R., Lakshmi, M., Mary, S.S.C., Jayakumar, M.: Smart diagnostic expert system for defect in forging process using machine learning. Journal of Nanomaterials. vol. 2022, p. 2567194 (2022)

[16] Ponomarev, M.G., Selcuk, C., Gan, T.-H., Amos, M., Nicholson, I., Iovea, M., Neagu, M., Stefanescu, B., Mateiasi, G.: Defect detection and classification system for automatic analysis of digital radiography images of PM parts. Powder Metallurgy. vol. 57, no. 1, pp. 17-20 (2014)

[17] Sassi, P., Tripicchio, P., Avizzano, C.A.: A smart monitoring system for automatic welding defect detection. IEEE Transactions on Industrial Electronics. vol. 66, no. 3, pp. 2296-2304 (2019)

[18] Sreedhar, U., Krishnamurthy, C., Balasubramaniam, K., Raghupathy, V., Ravisankar, S.: Automatic defect identification using thermal image analysis for online weld quality monitoring. Journal of Materials Processing Technology. vol. 212, no. 9, pp. 1557-1566 (2012)

[19] Althubiti, S.A., Alenezi, F., Shitharth, S., Sangeetha, K., Reddy, C.V.S.: Circuit manufacturing defect detection using VGG16 convolutional neural networks. Wireless Communications and Mobile Computing. Art. no. 1070405 (2022)

[20] Biswas, S., Acharjee, S., Ali, A., Chaudhari, S.S.: YOLOv8 based traffic signal detection in Indian road. In: Proc. IEEE Int. Conf. Electronics, Materials Engineering and Nano-Technology (IEMENTech), Art. no. 10423520 (2023). https://doi.org