

4. Construction of long distance bus rank in the vicinity of the intersection which will cater for long distances buses, taxis and mini buses. This would eliminate all the interruption in traffic movement at the intersection and also restore good visibility to road users and all vendors to be put within this rank.

References

- [1] American Association of State Highway and Transportation Officials (AASHTO).: A Policy on Geometric Design of Highways and Streets, Washington, D.C (2011)
- [2] South African National Road Agency (SANRAL).: South African Geometric Design Guidelines (2003)
- [3] Ausroads.: Guide to Traffic Engineering Practice, Part 4B-Roundabouts (2011)
- [4] Morris, M., Neil, J.R. and Pederson, E.: NCHRP Report 672-Roundabouts Information Guide (2010)
- [5] Federal Highway Administration.: An informational Guide for Roundabout Geometric Design, pp. 127-181 (2013)
- [6] Norwalk.: Intersection Design-Transportation Management and Planning, pp. 73 (2012)
- [7] Tom, V. and Mathew, K.: Traffic Intersections-Introduction to Transportation Engineering, pp. 1-7. Available at : http://nptel.ac.in/courses/105101087/downloads/Lec_39.pdf (2007)
- [8] Che, W.F.: The Civil Engineering Handbook, West Lafayette, Indiana, CRC Press (1995)
- [9] O'Flaherty, C.A.: Transport Planning and Traffic Engineering, Elsevier, Oxford (1997)
- [10] Vassileva, L.D.: Highway Design, Transportation Systems and Infrastructure, University of Zimbabwe, Harare (2015)
- [11] Salter, R.J.: Highway Traffic Analysis and Design, Macmillan Education Ltd, Hong Kong (1989)